



- Rotates through 360° and pivots 180°, and simultaneously allows lifting from any direction.
- Manufactured from forged alloy steel, quenched and tempered.
- Tested in accordance with EN1677-1.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.
- Quick and simple assembly, just a tapped hole is required.

» Taiwan Patent  
» China Patent

## Anchor Point Long Bolt

Metric Thread (8-231L)



Item No.	Working Load Limit tonnes	Thread version			Dimensions										Torque in Nm	N.W. kg	
		M	E	Pitch	A	B	C	D	F	G	H	R	S	SW			I
		mm	mm	DIN13	mm												
8-231-005/105L	0.5	M 8	83	1.25	33	42	28	11	80	58	23	17	6	13	44	30	0.3
8-231-007/125L	0.7	M 10	103	1.50	33	41	29	11	80	58	23	17	6	17	44	60	0.3
8-231-010/150L	1.0	M 12	128	1.75	33	39	31	11	80	58	23	17	8	19	44	100	0.4
8-231-020/185L	2.0	M 16	149	2.00	50	54	46	17	116	90	36	27	10	24	63	150	1.0
8-231-030/230L	3.0	M 20	194	2.50	51	52	49	17	116	90	37	27	12	30	63	250	2.0
8-231-050/265L	5.0	M 24	222	3.00	72	81	59	25	163	126	45	37	14	36	88	400	2.8
8-231-078/340L	7.8	M 30	278	3.50	87	94	81	30	204	148	62	46	17	46	110	500	4.8
8-231-125/300L	12.5	M 36	226	4.00	109	112	98	36	248	188	75	57	22	55	128	1000	10.6
8-231-156/350L	15.6	M 42	268	4.50	110	101	108	36	248	188	82	57	24	65	128	1500	11.3
8-231-200/385L	20.0	M 48	303	5.00	110	97	112	36	248	188	82	57	27	75	128	2000	13.3

\* Design Factor 4:1