



Clevis Master Link.



Item No.	Working Load Limit tonnes*	For Grade 80 Chain mm	Dimensions (mm)						N.W. kg
			A	G	H	K	L	T	
8-059-07	2.0	7, 8	10	65	15	103	83	19	0.4
8-059-10	3.15	10	11	96	19	133	108	19	0.8
8-059-13	5.3	13	15	108	22	168	136	25	1.5
8-059-16	8.0	16	18	124	26	203	165	27	2.4

★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677

Connecting Link



Item No.	Working Load Limit tonnes*	For Grade 80 Chain mm	Dimensions (mm)				N.W. kg
			A	B	D	K	
8-015-06	1.12	6	15	17	7	45	0.08
8-015-07	2.0	7, 8	18	22	9	58	0.2
8-015-10	3.15	10	26	27	11	69	0.3
8-015-13	5.3	13	30	37	15	91	0.7
8-015-16	8.0	16	36	39	19	101	1.1
8-015-20	12.5	18, 20	42	46	22	122	1.9
8-015-22	15.0	22	49	59	24	152	3.0
8-015-26	21.2	26	55	63	30	164	5.0
8-015-32	31.5	32	69	79	36	203	9.0



Type Approval


★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677

Connecting Link

Dacromet® Surface Finish.**



special pin and sleeve designed for more often re-use purpose.



Item No.	Working Load Limit tonnes*	For Grade 80 Chain mm	Dimensions (mm)				N.W. kg
			A	B	D	K	
8-M015-06	1.12	6	15	17	7	45	0.16
8-M015-07	2.0	7, 8	18	24	9	58	0.16
8-M015-10	3.15	10	26	28	11	69	0.3
8-M015-13	5.3	13	30	38	15	91	0.7
8-M015-16	8.0	16	36	41	19	101	1.2
8-M015-20	12.5	18, 20	42	50	22	122	1.9
8-M015-22	15.0	22	49	63	24	152	3.0
8-M015-26	21.2	26	55	66	30	164	4.6
8-M015-32	31.5	32	69	85	36	203	8.5



Type Approval



★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677