


## How to use YOKE Self Locking Hook?













## **Eye Self Locking Hook.**







Item	No.	Working Load Limit	For Grade 80 Chain	Dimensions (mm)						N.W.
		tonnes*	mm	Α	D	Н	K	Р	Т	kg
8-02	5-06	1.12	6	21	10	19	110	28	15	0.5
8-02	5-07	2.0	7,8	25	11	24	136	34	20	0.8
8-02	5-10	3.15	10	33	13	30	167	44	26	1.4
8-02	5-13	5.3	13	40	16	39	207	51	30	3.0
8-02	5-16	8.0	16	50	21	49	252	61	36	5.8
8-02	5-20	12.5	18, 20	62	23	62	281	91	48	8.5
8-02	5-22	15.0	22	70	24	63	319	80	49	12.5
8-02	5-26	21.2	26	80	25	69	343	99	56	14.0
8-02	5-28	25.0	28	92	28	81	405	123	63	26.0

★ Design factor 4:1 proof tested and certified Tested acc. to EN 1677

## Clevis Self Locking Hook.



Item No.	Working Load Limit	For Grade 80 Chain		N.W.				
	tonnes*	mm	Α	Н	K	Р	Т	kg
8-026-06	1.12	6	7	19	93	28	15	0.5
8-026-07	2.0	7, 8	9	24	119	34	20	0.8
8-026-10	3.15	10	12	30	143	44	26	1.4
8-026-13	5.3	13	15	39	179	51	30	2.9
8-026-16	8.0	16	18	49	212	61	36	5.6
8-026-20	12.5	18, 20	21	62	243	91	48	9.0
8-026-22	15.0	22	24	63	273	80	49	13.0



★ Design factor 4:1 proof tested and certified Tested acc. to EN 1677

