


Eye Sling Hook.

with Latch



Type Approval




Item No.	Working Load Limit tonnes*	For Grade 80 Chain mm	Dimensions (mm)						N.W. kg
			A	D	H	K	P1	T	
8-044/S-06	1.12	6	20	10	19	80	23	17	0.3
8-044/S-07	2.0	7, 8	25	12	22	98	28	20	0.5
8-044/S-10	3.15	10	32	15	30	121	36	23	1.0
8-044/S-13	5.3	13	40	18	38	152	40	28	1.7
8-044/S-16	8.0	16	50	22	45	185	44	32	3.2
8-044/S-20	12.5	18, 20	62	27	49	225	45	46	5.5
8-044/S-22	15.0	22	51	31	62	244	73	52	9.0
8-044/S-26	21.2	26	64	35	77	285	77	61	13.5
8-044/S-32	31.5	32	89	40	80	352	114	65	20.0

★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677



Eye Foundry Hook.



Type Approval

Item No.	Working Load Limit tonnes*	For Grade 80 Chain mm	Dimensions (mm)						N.W. kg
			A	D	H	K	P	T	
8-047-07	2.0	7, 8	24	12	27	122	61	19	0.7
8-047-10	3.15	10	32	15	32	150	74	23	1.3
8-047-13	5.3	13	40	19	39	180	88	32	2.3
8-047-16	8.0	16	50	24	46	215	98	41	4.1
8-047-20	12.5	18,20	60	26	59	248	112	58	9.3

★ Design factor 4:1 proof tested and certified
Tested acc. to EN 1677