


Oblong Master Link.

Connected to Chain with "YA" connecting link.



Extra width inside allows better works on large crane hooks.



Type Approval




Item No.	WLL β 0-45° tonnes*	For Grade 80 Chain(mm)		Dimensions (mm)			N.W. kg
		1 Leg	2 Leg	D	IL	IW	
8-003-06	※ 1.25	6	--	11	100	60	0.2
8-003-0806	※ 2.5	7, 8	6	14	120	70	0.4
8-003-1008	※ 4.0	10	7, 8	17	140	80	0.7
8-003-13	※ 5.4	13	--	19	150	90	1.1
8-003-1310	※ 7.5	13	10	22	160	95	1.5
8-003-16	※ 10.0	16	--	25	190	110	2.2
8-003-1613	※ 10.0	16	13	28	180	105	2.8
8-003-19	※ 12.0	19, 20	--	30	200	120	3.8
8-003-2216	※ 17.0	22	16	34	240	140	5.5
8-003-26	※ 25.0	26	--	38	250	150	7.0
8-003-2619	※ 28.0	26	19, 20	40	250	150	8.0
8-003-3222	※ 37.0	32	22	45	300	180	12.7

※ Forged Oblong Master Links.

Design factor 4:1 proof tested and certified Tested acc. to EN 1677

Oblong Master Link with Flat.

Connected to Chain with "YO" Omega Link.



Type Approval



Item No.	WLL β 0-45° tonnes*	For Grade 80 Chain(mm)		Dimensions (mm)			N.W. kg
		1 Leg	2 Leg	D	IL	IW	
8-003F-06	※ 1.25	6	--	11	100	60	0.2
8-003F-0806	※ 2.5	7, 8	6	14	120	70	0.4
8-003F-1008	※ 4.0	10	7, 8	17	140	80	0.7
8-003F-1310	※ 7.5	13	10	22	160	95	1.5
8-003F-1613	※ 10.0	16	13	28	184	105	2.8
8-003F-2216	※ 17.0	20	16	34	245	140	5.3
8-003F-2619	※ 25.0	--	19, 20	40	250	150	8.0

※ Forged Oblong Master Links.

★ Design factor 4:1 Proof tested and certified

WLL=Working Load Limit Tested acc. to EN 1677