



- Pivots to 230°, rotates through 360° due to its unique ball bearing design.
- Manufactured from forged alloy steel, quenched and tempered.
- Tested in accordance with EN1677-4.
- Certified by DGUV GS-OA-15-04.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and batch code links to Test Certificate sheet.
- Bolts are Metric thread.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.
- Easy to attach or dismantle due to the forged hexagon shaped body of the Swivel Point.
- Capable of rotating under load. Do not turn continuously in 90 degree direction at full load.

Swivel Point

Metric Thread (8-271)



Item No.	Working Load Limit tonnes	Thread version			Dimensions (mm)								Torque in Nm	N.W. kg
		M mm	E mm	Pitch DIN13	G	C	K	H	F	D	B	A		
8-271-003	0.4	M 8	12	1.25	35	40	30	16	72	8	32	29	10	0.2
8-271-004	0.6	M 10	15	1.50	35	40	30	16	72	8	32	29	10	0.2
8-271-006	0.7	M 12	18	1.75	40	45	36	18	95	10	50	35	10	0.3
8-271-013	1.5	M 16	24	2.00	46	54	41	22	104	13	50	36	30	0.5
8-271-020	2.5	M 20	30	2.50	62	68	55	29	122	13	54	36	70	1.0
8-271-035	4.0	M 24	36	3.00	78	88	70	36	154	19	66	41	150	2.2
8-271-060	6.0	M 30	45	3.50	90	120	80	48	206	22	86	50	350	4.5
8-271-080	10.0	M 36	54	4.00	90	120	80	48	206	22	86	50	410	4.6
8-271-120	13.0	M 42	63	4.50	98	122	84	50	235	25	110	67	550	5.5
8-271-130	14.0	M 48	72	5.00	98	122	84	50	235	25	110	67	550	6.1
8-271-140	20.0	M 52	78	5.00	120	150	94	60	270	32	120	72	750	10.5
8-271-160	20.0	M 56	84	5.50	120	150	94	60	270	32	120	72	800	10.7
8-271-161	20.0	M 64	96	6.00	120	150	94	60	270	32	120	72	800	11.6
8-271-310	40.0	M 72	108	6.00	170	210	145	83	340	45	130	90	1200	30.6
8-271-350	40.0	M 80	120	6.00	170	210	145	83	340	45	130	90	1500	31.6
8-271-400	40.0	M 90	135	6.00	170	210	145	83	340	45	130	90	2000	33.9

* Design Factor 4:1

