


**Eye Sling Hook. Code "YP"**

with Latch




Item No.	Working Load Limit tonnes*	For Grade 80 Chain mm	Dimensions (mm)						N.W. kg
			A	D	H	K	P1	T	
<b>8-044/S-06</b>	1.12	6	20	9	20	80	23	16	0.3
<b>8-044/S-07</b>	2.0	7, 8	25	11	23	98	28	20	0.5
<b>8-044/S-10</b>	3.15	10	32	14	31	121	36	23	1.0
<b>8-044/S-13</b>	5.3	13	40	18	38	152	40	28	1.7
<b>8-044/S-16</b>	8.0	16	50	22	47	184	44	32	3.2
<b>8-044/S-20</b>	12.5	18, 20	60	26	48	218	45	43	5.5
<b>8-044/S-22</b>	15.0	22	50	31	62	244	73	50	9.0
<b>8-044/S-26</b>	21.2	26	64	35	80	279	77	60	13.5
<b>8-044/S-32</b>	31.5	32	88	40	86	352	114	65	20.0



**ABS**

Type Approval

★ Design factor 4:1 proof tested and certified  
Tested acc. to EN 1677



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 2 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.



**8-P044**  
Repair kit available

## G-100 Eye Sling Hook

with Latch

Item No.	For Grade 100 Chain		Dimensions (mm)						N.W. kg
	mm	tonnes*	A	D	H	K	P1	T	
X-044/S-06	6	1.4	20	10	19	80	23	17	0.3
X-044/S-07	7, 8	2.5	25	12	23	98	28	20	0.5
X-044/S-10	10	4.0	32	15	31	121	36	23	1.0
X-044/S-13	13	6.7	40	18	38	152	40	27	1.8
X-044/S-16	16	10.0	50	22	45	185	44	32	3.4
X-044/S-20	20	16.0	61	27	64	230	54	48	7.3
X-044/S-22	22	19.0	51	31	63	245	76	52	9.3
X-044/S-26	26	26.5	65	35	80	279	77	60	13.5
X-044/S-32	32	40.0	88	40	86	352	114	65	22.0

★ Design factor 4:1 proof tested and certified.