

8-027 / Swivel Self Locking Hook Grade 80 Lifting Chain & Fittings




Description

★ Design factor 4:1 proof tested and certified Tested acc. to DIN EN 1677

Remark

Code" YE "



Specification

Item No.	Working Load Limit tonnes*	For Grade 80 Chain(mm) mm	Dimensions (mm)							N.W Kg
			A	B	D	H	K	P	T	
8-027-06	1.12	6	31	22	12	19	149	29	15	0.7
8-027-07	2.0	7, 8	36	29	14	24	186	34	20	1.2
8-027-10	3.15	10	40	34	16	30	220	44	26	2.0
8-027-13	5.3	13	46	43	22	39	267	52	30	4.1
8-027-16	8.0	16	60	50	24	49	328	60	36	7.2
8-027-20	12.5	18, 20	75	82	26	62	388	90	48	11.4
8-027-22	15.0	22	97	95	33	63	457	80	49	18.0
8-027-26	21.2	26	123	115	52	69	535	99	56	31.0

X-027 / G-100 Swivel Self Locking Hook Grade100 Lifting Chain Fittings



Description

★ Design factor 4:1 proof tested and certified. WARNING INFORMATION: This hook is a positioning device and is not intended to rotate under load. For swivel hooks designed to rotate under load, please refer to X-027N.



Specification

3D file Download	Item No.	Working Load Limit tonnes*	For Grade 100 Chain (mm) mm	Dimensions (mm)							N.
				A	B	D	H	K	P	T	
	X-027-06	1.4	6	32	25	12	19	149	28	15	0
	X-027-07	2.5	7, 8	36	30	13	24	186	34	20	1
	X-027-10	4.0	10	41	38	16	30	218	44	26	2
	X-027-13	6.7	13	46	48	21	39	276	51	30	4
	X-027-16	10.0	16	61	56	23	49	329	60	36	7
	X-027-20	16.0	20	74	86	25	65	403	70	53	13
	X-027-22	19.0	22	97	98	33	63	455	80	49	20
	X-027-26	26.5	26	123	120	51	69	535	99	56	33

Back