


ROUND STRAND

6/19F (12-6F+6-1)

NOM. ROPE DIA	APPROX. MASS Kg./100m	MINIMUM BREAKING FORCE		
		1570 N/mm ²	1770 N/mm ²	1960 N/mm ²
mm	FIBRE CORE	kN	kN	kN
8	24.3	34	38	42
10	38.0	53	60	66
12	54.7	76	86	95
13	64.3	90	101	112
14	74.5	104	117	130
16	97.3	136	153	169
18	123	172	194	214
19	137	191	216	239
20	152	212	239	265
22	184	257	289	320
24	219	305	344	381
26	257	358	404	447
28	298	416	469	519
32	389	543	612	678
34	439	613	691	765
36	493	687	775	858
38	549	766	863	956
40	608	848	956	1059
44	736	1026	1157	1281
46	804	1122	1265	1401
48	876	1222	1377	1525
52	1028	1434	1616	1790
58	1279	1784	2011	2227
60	1369	1909	2152	2383
64	1557	2172	2448	2711

Note:

All intermediate sizes are also available



ROUND STRAND

6/19F (12-6F+6-1)

NOM. ROPE DIA	APPROX. MASS Kg./100m	MINIMUM BREAKING FORCE		
		1570 N/mm ²	1770 N/mm ²	1960 N/mm ²
mm	STEEL CORE	kN	kN	kN
8	26.7	37	41	46
10	41.8	57	65	71
12	60.2	82	93	103
13	70.7	97	109	121
14	82.0	112	127	140
16	107	147	165	183
18	135	186	209	232
19	151	206	233	258
20	167	229	258	286
22	202	277	312	346
24	241	330	372	412
26	283	387	436	483
28	328	449	506	560
32	428	586	661	732
34	484	662	746	826
36	542	742	837	926
38	604	827	932	1032
40	669	916	1030	1144
44	810	1110	1250	1384
46	885	1212	1366	1513
48	964	1319	1487	1647
52	1131	1448	1745	1933
58	1407	1927	2172	2403
60	1506	2061	2324	2573
64	1714	2345	2644	2928

Note:

All intermediate sizes are also available